

# PRODUCT INFO SHEET

Nanmac Corporation

Quality • Performance • Solutions

## Jack Panels F8 Series

Available in two materials, the standard material is good to 400 degrees Fahrenheit. The high temperature material is good to 800 degrees Fahrenheit. All high temperature jacks are color coded 'red.' All standard jacks are coded per thermocouple calibration. Standard thermocouple calibration symbols and color codes are easily visible from the front.

### NOTES:

- All panels are 3/32 inch steel frame.
- All thermocouple calibrations and copper jacks are available.
- For 800°F units, add suffix "-HT" for High Temperature, to the part number.
- Numbering sequence begins at 1 unless otherwise noted.
- Special panels with up to 240 circuits are available, contact factory.
- When ordering, specify part number and calibration.  
*Example: F8-2-K*



Mini Size Shown

Specifications				
Part No.	Jack Size	Number of Jacks	Panel Cutout	
			Height (in.)	Width (in.)
F8-1	Standard	2	1-1/2	1-1/2
F8-2		3	1-1/2	2-1/4
F8-3		4	1-1/2	3
F8-4		5	1-1/2	3-3/4
F8-5		6	1-1/2	4-1/2
F8-6	Mini	6	1	3-7/8
F8-7		12	1	7-5/8
F8-8		18	1	11-3/8
F8-9*		24	2-1/2	7-5/8

11 Mayhew Street  
Framingham, MA 01702  
www.Nanmac.com  
engineering@nanmac.com

Foremost in Temperature Measurement™  
**NANMAC**

US & Canada: 1.800.786.4669  
International: 1.508.872.4811  
Fax: 1.508.879.5450  
info@nanmac.com